

SCALEOVIEW T17-1 17 Inch LCD TFT Monitor

Issue September 2004

Pages 2

The best choice for families.

The SCALEOVIEW T17-1 offers upgraded performance for home office, multimedia and fast internet. And what's more, thanks to its amazing picture quality and super-fast response times, it delivers one of the best gaming experiences around.

Reliability

- Guaranteed quality and stability
- Reliability of delivery
- Low power consumption
- Multi-level power management
- Experience service partners

Usability

- Administrator is able to read inventory data
- Easy-to-use menu
- Auto-adjust
- Plug & Play
- Standardised mounting interface
- Integrated audio
- Fast response time

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent colour purity
- Outstanding brightness uniformity
- Extremely wide viewing angle
- Integrated speakers
- High contrast and excellent focus

- Environmental friendly with low-radiation
- Immunity to external electromagnetic fields

Diversity

- Displays for differentiated demands
- Meets highest demands in terms of ergonomics, usability and resolution
- Comparable with 19-inch CRT display

Valuable and accepted Brand

- Profiting from the experience as leading European consumer brand
- Strong cooperation with leading edge technology suppliers for latest technologies
- Strong relationship with internationally acting retail partners for fast delivery and best support

Market innovator

- Leading edge technology
- High quality and stylish design
- Latest technologies with fast delivery
- All delivered in an attractive packaging design



Visible screen diagonal	17 inch (43 cm)
Graphics display (dependent on graphics processor)	
Pixels	1280 x 1024
Pixels *)	800 x 600
Pixels *)	640 x 480
*) expanded	
Highest Resolution	1280 x 1024
Text display (dependent on graphics processor)	
Pixels (max. 75Hz)	720 x 400
Picture size	338 x 270 mm
Colors	16,2 millions
Pixel Pitch	0,264 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	55 - 76 Hz
Brightness typical	350 cd/m ²
Contrast typical	350:1
Viewing angle typical	
Horizontal	160°
Vertical	120°
Response time typical	14ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light)	
Contrast	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Auto balance	
Activate factory settings	
Menu language	
Base	
Tilt angle	-0°/ +20 °
Audio characteristics	
volume control	digital
Audio signal input (from PC)	3.5 mm stereo phone jack
Sound output	2,5 W (L) + 2,5 W (R)

Electrical values

Rated voltage	100-240 V
Frequency	50-60 Hz
Power draw	
Max.	51 W
Stand by	3 W
Protection class	1

Temperatures/dimensions/weight

Ambient temperature (to IEC721)	
Working	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D)	400.5 x 409.7 x 215.6 mm
(With Stand)	
Weight (Monitor only)	3.5 kg

Reliability

MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	40,000 h
(brightness > 50 % of original brightness)	

Compliance with standards

Product safety	EN60950
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99

Data cable (1.8 m)	D-SUB (15-pin)
detachable on display	audio cable (1.8 m)

Power cable (1.8 m)	For wall socket
	Euro-Schuko-Type CEE7

External power adapter	
Plug type on power adapter	IEC-320-C13

Special features	Standardized mounting interface according VESA FPMPI (75 mm)
-------------------------	--

Order code	S26361-K974-V170
-------------------	-------------------------

